



19" KVM Console with 19" TFT-LCD Panel DE/US Keyboard Layout

The LCD console module features an integrated 19" TFT-LCD panel with ultra-thin keyboard and touchpad in 1U Rack-mountable housing.

Technical Features

A control platform with LCD, keyboard, mouse and a single port KVM switch

Grade A 19" TFT LCD with the maximum resolution of 1366 x 768@60Hz

Ultra-thin keyboard and touchpad in a 1U rack-mountable Slideway™ housing; easily to pull out or slide in

1U height, suitable for 19" standard cabinet installation and metal structure

Compatible with most KVM switches

LCD module rotates up to 110° for a more comfortable viewing angle

Front panel with a lock to prevent damages by any accident

Easy to use with the On-Screen-Menu (OSD)

Support PS/2 and USB

When pulling control platform out from cabinet, the power turns on automatically. When pushing it into the cabinet, the power turns off automatically

Enclosed mounting rails are suitable for racks with 800 and 1000 mm depth

Art-No.	Keyboard Layout	EAN Code
LC902GE	DE	4052792045277
LC902US	US	4052792045284
LC0002	Mounting Rail 1200 mm	4052792049268



www.2direct.de



RoHS
compliant



Made in China

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Specification

Computer Connection	1	
CPU Port Selection	Front panel buttons/OSD menu	
Console Connector	Keyboard	Disassembled standard 100-key keyboard
	Mouse	Standard PS/2 touch pad USB connector on the front
	Video	18.51" WXGA color TFT-LCD
Cable Connector	Keyboard	1x PS/2 female (purple), 1x USB female
	Mouse	1x PS/2 female (green)
	Video	1x HDB-15 male (blue)
LCD Monitor	Monitor	18.51" WXGA Color TFT-LCD
	Active Area	409.8(H)x230.4(V) mm
	Pixel H x V	1366x3(RGB)x768
	Support Color	16.7M colors (RGB 6-bit+Hi-FRC)
	White Luminance	250cd/m ² (Typ.)
	Contrast	1000:1 (Typ)
	Back Light	LED
	Pixel Pitch	300 um (per one triad)x300 um
	LCD MTBF	50,000 hours
	Input Power	DC 12V
Mouse	X/Y Resolution	1000 dots/inch 40x40/ mm
	Hardware Connector	Standard PS/2
	OS Support	Win95/98/98SE/ME/2000/XP/Vista/NT/7/10 Unix, Linux
	Life Span	1,000,000 times
Keyboard	Keyboard	100 keys
	Compatible IBM/AT	Win95/98/98SE/ME/2000/XP/Vista/NT/7/10 Unix, Linux
	Port	Standard PS/2 and USB
	Life Span	> 1,000,000 times
LED	Online	LED Display
	Selected	Nixie Tube Display



LCD Monitor	Monitor	18.51" WXGA Color TFT-LCD
	Active Area	409.8(H)x230.4(V) mm
	Pixel H x V	1366x3(RGB)x768
Power	Power (AC)	100–240 V
	Life Span	MTBF>60,000 hours 25°C
Housing	Metal (Black)	
Dimension	407x445x44 mm	
Installation Dimension	400–800 mm (adjustable)	
Operating Temperature	0–50°C	
Storage Temperature	-20–60°C	

Package Contents

1x 19" LCD Console

1x Power Adapter

1x DP37 Pins Connection Cable

1x User Manual

Packaging Informations

Packing Dimension	407x445x44 mm
Packing Weight	8.32 kg
Carton Dimension	740x610x185 mm
Carton Q'ty	1 pcs
Carton Weight	14.12 kg

